

BULLETIN


The NEW Standard in Water Service Tubing

Gold901[™] is a lightweight, easy to install, 250 psi rated water service tubing that can be used on both the municipal and private-side of a project.

Gold901 is manufactured to Copper Tube Size (CTS) from High-Density Polyethylene (HDPE) and is third-party certified and listed to AWWA C901, CSA B137.1 and NSF 61.

Gold901 is conveniently available in both coils and reels and is available in 3/4" to 2".

Standards



1 (SP) CSA B137.1



NSF-61

Product Selection Chart

Nominal Pi inches	pe Size mm	Coil Length feet	Product Code Av	O.D. verage (in) Av	I.D. erage (in)	Min. Radius of Bend (in)
3/4	20	100	121402			19
		200	121403		0.671	
		400	121404	0.875		
		500	121405			
		3000	121406			
1	25	100	121407	1.125	0.863	23
		150	121408			
		200	121409			
		300	121410			
		500	121411			
		1000	121412			
		1500	121413			
1 1/4	32	100	121414	1 775	1.055	30
		300	121415	1.375		
1 1/2	40	100	121416	1.625	1.245	34
		250	121417			
		400	121418			
		1000	121419			
2	50	100	121420	2.125	1.629	44
		200	121421			
		500	121422			

Features & Benefits:

Non-corroding

Resistant to corrosive soils, aggressive water, stray electrical currents and moist environments

Lightweight

A 200 foot coil of 3/4" Gold901 weighs 20 lbs

Sequential Markings

Every 2 or 5 feet

Superior Flow

Hazen Williams C-Factor = 150

High Pressure

Rated at 250 psi at 73°F (1.725 kPa at 23°C)



Contact us

Visit our website: ipexna.com

Toll Free: (866) 473-9462

Products are manufactured by IPEX Inc. Gold901™ is a trademark of IPEX Branding Inc.

