

## Kwikflex® NMLT Extra Flexible Electrical Tubing

Kwikflex™ nonmetallic liquidtight flexible (NMLT) conduit and fittings offer superior flexibility and corrosion resistance for protecting electrical wiring and connections to commercial and residential pool and spa motors, air conditioners, pumps and outdoor lighting.

Approved for use in dry, damp or wet locations, Kwikflex™ provides a positive, waterproof seal and easy, screw-together connectivity in indoor/outdoor, exposed or concealed environments. Kwikflex NMLT is UL listed and permitted for use by the NEC (Article 356) in exposed and concealed locations for the protection of conductors where a degree of flexibility is required.

### FEATURES & BENEFITS

- 1/4" thru 2" trade size
- Use with Kwikflex® straight or right angle connectors
- Resists corrosion, oil, & water
- Maximum flexibility, can be used in extremely tight quarters
- Resists abuse, pull & crushing
- Smooth inside for easier wire pulling
- Light weight, lower installed cost
- Outdoor, sunlight resistant
- Quick installation, cuts with utility knife or PVC cutter
- Integral rigid & flexible PVC construction
- Suitable for use in high vibration or flexing applications
- Ideal for fiber optic cable protection

### STANDARDS



C22.2  
No. 227.1

### APPLICATIONS

- Automotive equipment
- Computer & peripherals
- Fiber optics
- Lab equipment
- Lasers
- Office equipment
- Processing control and monitoring equipment
- Robotics
- White goods systems

## SPECIFICATIONS

Product Code	Trade Size	Std. Pkg.	Weight / Pkg.	Part Dimensions (inches)	
				O.D. Min.-Max.	I.D. Min.-Max.
165055	3/8"	100	9	.690 - .710	.484 - .504
165057	1/2"	100	10	.820 - .840	.622 - .642
165059	3/4"	100	14	1.030 - 1.050	.820 - .840
165061	1"	100	19	1.290 - 1.315	1.041 - 1.066
165064	1-1/4"	100	22	1.630 - 1.660	1.380 - 1.410
165067	1-1/2"	50	14	1.865 - 1.900	1.575 - 1.600
165070	2"	50	21	2.340 - 2.375	2.020 - 2.045

Standard Color Black

