


Kwikflex® NMLT Screw-On Conduit Connectors

Kwikflex™ nonmetallic liquidtight flexible (NMLT) conduit and fittings offer superior flexibility and corrosion resistance for protecting electrical wiring and connections to commercial and residential pool and spa motors, air conditioners, pumps and outdoor lighting.

Approved for use in dry, damp or wet locations, Kwikflex™ provides a positive, waterproof seal and easy, screw-together connectivity in indoor/outdoor, exposed or concealed environments. Kwikflex NMLT is UL listed and permitted for use by the NEC (Article 356) in exposed and concealed locations for the protection of conductors where a degree of flexibility is required.

FEATURES & BENEFITS

- Available in 1/2" & 3/4" trade size
- UL & CUL listed
- PVC construction produced from UV rated material for long outdoor life
- Attractive one-piece design
- No disassembly required; simply screw the connector onto the conduit
- Time & cost saving benefits over other brands
- Design allows superior liquid-tight seal & optimum pull strength without compression nut
- Ideal for conduit assemblies & installers
- "O" Ring & steel locknut included
- Standard color - Gray




STANDARDS



APPLICATIONS

- HVAC equipment
- Machine tools
- Marine equipment
- Motors & controls
- Printing equipment
- Pumps
- Refrigeration equipment
- Assemblies
- Wire hook-up



SPECIFICATIONS

Part No.	Product Code	Description (screw on)	Trade Size	K.O. Size	Std. Pkg	Weight / Pkg.	Part Dimensions (inches)		
							A	B	C
LTD10	065360	Straight	1/2"	1/2"	25/100	5	1.750	0.500	1.250
LTD15	065362	Straight	3/4"	3/4"	25/100	7	1.800	0.625	1.500
LTD10/90	065350	90° Sweep	1/2"	1/2"	10/100	7	1.875	0.500	3.125
LTD15/90	065352	90° Sweep	3/4"	3/4"	10/100	9	2.375	0.625	3.500

Available in Black upon request