

BULLETIN

IPEX CPVC VENTILATION DUCT

IPEX offers Corzan® CPVC Ventilation Ducts for high temperature and corrosive fume handling applications. IPEX CPVC Ventilation Duct safely conveys exhaust fumes generated by various industrial processes, protecting workers and avoiding any inherent dangers to the environment from contaminated air.



Applications

- Chemical Processing
- Semiconductor Fabrications
- Metal Plating & Finishing
- Laboratory Installations
- · Pulp & Paper
- Wastewater Treatment Plants

IPEX CPVC Ventilation Duct is part of our complete industrial systems of pipe, valves, and fittings, engineered and manufactured to our strict quality, performance and dimensional standards.

CPVC Ventilation Duct Dimensions

Product Code	Average O.D. (in.)	Average I.D. (in.)	Average Wall Thickness (in.)	Weight (lbs/ft)
247700	6.625	6.251	0.187	2.519
247702	8.625	8.251	0.187	3.301
247704	10.750	10.376	0.187	4.133
247706	12.750	12.376	0.187	4.916
247707	14.000	13.626	0.187	5.405
247708	16.000	15.626	0.187	6.188
	Code 247700 247702 247704 247706 247707	Code O.D. (in.) 247700 6.625 247702 8.625 247704 10.750 247706 12.750 247707 14.000	Code O.D. (in.) I.D. (in.) 247700 6.625 6.251 247702 8.625 8.251 247704 10.750 10.376 247706 12.750 12.376 247707 14.000 13.626	Code O.D. (in.) I.D. (in.) Thickness (in.) 247700 6.625 6.251 0.187 247702 8.625 8.251 0.187 247704 10.750 10.376 0.187 247706 12.750 12.376 0.187 247707 14.000 13.626 0.187

These products are for atmospheric venting only. Do not use in pressurized air or gas systems.

Features and Benefits:

- Extruded seamless CPVC duct in all standard diameters 6" through 16"
- CPVC withstands exhaust temperatures up to 200°F
- CPVC cell class 23447 as per ASTM D1784
- CPVC is inert to most mineral acids, bases, salts, and aliphatic hydrocarbons, and compares favorably to other non-metals in corrosive chemical environments
- Low installed cost as compared to non-corrosive exotic metal and PVDF systems
- Light weight allows for ease of handling and installation and reduces transportation and labor costs
- Low maintenance requirements over extended service periods
- Low flame spread rating of 10 and smoke development classification of 25 as per CAN/ULC S102.2
- Corzan CPVC compound meets and is listed to FM 4910 "Clean Room Materials Flammability Test Protocol"

Contact us

Visit our website: ipexna.com

Toll Free: (800) 463-9572

Corzan® is a registered trademark of the Lubrizol Corporation.

