

10100 Rodney Street Pineville NC 28134

#### **IPEX USA LLC**

homeflexunderground@ipexamerica.com homeflexunderground.com

**Product** HOME-FLEX™ Underground Coupler Fitting, 1/2" - 2" IPS

	rmation

Job Name:	Date Submitted:	
Location:	Submitted by:	
Engineer:	Approved by:	
Contractor:	Manufacturer's Rep:	

# Installation

Must be installed in accordance with the HOME-FLEX™ Underground Installation Practices and Guidelines and in accordance with local codes.

# **Application Information**

Gas compression fittings for use in Natural Gas and Liquified Petroleum (Propane) Gas applications with Polyethylene (PE) gas pipelines.



# **Technical Data**

# Materials

Nut and Main Body
O-Ring
Nitrile
Spacer
Nylon
Grip Ring
Stiffener
Acetal





Pressure Ratings

Max Operating Pressure 125 PSIG

Temperature Ratings

Operating Temperature Range -20°F - 180°F

### Codes

Uniform Plumbing Code (UPC), International Fuel Gas Code (IFGC)

## **Standards**

ASTM F1924-12 (Category 1 fittings)

# Listings

IAPM0 10218

# Made in Australia

# **Dimensional Information**

Size (IPS)	Part Number	Dimensions (in)				Weight
Size (IP3)		S	D	D2	L	(lbs)
1/2" SDR 9.3	250155	0.39	1.81	1.81	4.37	0.18
1/2" IPS to 1/2" CTS	250162	0.40	1.81	1.51	4.40	0.20
3/4" SDR 11	250156	0.43	2.13	2.13	4.69	0.29
1" SDR 11	050157	0.55	2.68	2.68	5.75	0.46
1-1/4" SDR 11	250158	0.71	3.23	3.23	7.17	0.93
1-1/2" SDR 11	250160	0.94	3.78	3.78	8.07	1.30
2" SDR 11	250161	1.14	4.44	4.44	9.17	1.96



1802/J