

The NEW Standard in Water Service Tubing

Gold901™ is a lightweight, easy to install, 250 psi rated water service tubing that can be used on both the municipal and private-side of a project.

Gold901 is manufactured to Copper Tube Size (CTS) from High-Density Polyethylene (HDPE) and is third-party certified and listed to AWWA C901, CSA B137.1 and NSF 61.

Gold901 is conveniently available in sizes 3/4" to 2".

Standards



Product Selection Chart

inches	Coil Length feet	Product Code	O.D. Average (in)	I.D. Average (in)	Min. Radius of Bend (in)
3/4	100	121402	0.875	0.671	19
	300	121653			
	500	121405			
1	100	121407	1.125	0.863	23
	200	121409			
	300	121410			
	500	121411			
1 1/4	100	121414	1.375	1.055	30
	300	121415			
	500	121652			
1 1/2	100	121416	1.625	1.245	34
	300	121651			
	500	121650			
	100	121420			
2	200	121421	2.125	1.629	44
	300	121649			

Features & Benefits:

- **Non-corroding**
Resistant to corrosive soils, aggressive water, stray electrical currents and moist environments
- **Lightweight**
A 100 foot coil of 3/4" Gold901 weighs 10 lbs
- **Sequential Markings**
Every 2 or 5 feet
- **Superior Flow**
Hazen Williams
C-Factor = 150
- **High Pressure**
Rated at 250 psi at 73°F
(1,725 kPa at 23°C)



Contact us

Visit our website: ipexna.com

Toll Free U.S.: (800) 463-9572

Products are manufactured by IPEX Inc. and distributed by IPEX USA LLC.
Gold901™ is a trademark of IPEX Branding Inc.