BLAZEMASTER® CPVC Pipe & Fittings

Advantages:

- The most specified nonmetallic fire sprinkler piping system in the world
- cULusUL, cUL, FM, NSF & LPCB approved
- cULus listed for exposed installations in unfinished basements in accordance with NFPA 13D
- cULus listed for use embedded in concrete
- Fit for use in wet and dry systems



THE DEPENDABLE CHOICE

That's what you get when you choose IPEX BlazeMaster® CPVC for your fire sprinkler system. Our broad portfolio of products offered in a wide range of sizes is backed by IPEX's industry-leading 10-year warranty and the BlazeMaster FBC™ System Compatible Program, the most robust compatibility program in the industry. Choose IPEX BlazeMaster CPVC when you want the job done right. Looking to save time and money on the jobsite? Try our new line of IPEX Rapid Seal sprinkler head adapters. Designed to reduce installation time, the Rapid Seal Adapter's all-CPVC design eliminates the need for thread tape or sealant and provides an easy, leakfree installation. Simply hand-tighten and adjust with a wrench. Turn. Tighten. Done.

Scan here for more information





1-800-463-9572 | ipexna.com



CPVC Compatibility

Understanding CPVC compatibility is extremely important when installing your residential sprinkler system. To ease the burden associated with researching and selecting accompanying construction products, Lubrizol developed the FBC™ System Compatible Program.

Rapid Seal Adapter Features:

- No thread tape or sealant
- No dezincification
- · Available in various styles





CPVC/FBC-System-Compatible-Program for more information and to view identified compatible and incompatible products.



Always refer to the Technical Data Sheets for a complete description of all listing criteria, design parameters, installation instructions, care and maintenance guidelines, and our limited warranty.

BlazeMaster® is manufactured by IPEX USA LLC. and distributed in Canada by IPEX Inc. BlazeMaster® is a registered trademark of the Lubrizol Corporation.

CPVC Products

Pipe	Fittings	Rapid Seal Adapter
Size Diameter 3/4" (19,05 mm) up to 3" (76,2 mm)	3/4" (19,05 mm) up to 3" (50,8 mm) connections	Elbow Adapters (Straight and 90°) 3/4" (19,05 mm) 1" (25,4 mm) Spigot Adapters (NPT connection) 1" (25,4 mm)
Standard Lengths 8' (2,44 m)* 10' (3,05 m) 15' (4,57 m) *limited availablilty	Accessories	
	Metal hangers Solvent cement Tools	



